

DW PRIMER



Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
1 kg/plastic can	12 pcs/box	0.2-0.3 kg/m ²	Yellow
5 kg/plastic can	4pcs/box	-	-
10 kg/plastic can	60 pcs/pallet	-	-



DESCRIPTION

DW Primer is an acrylic resin -based primer, which is used to give the support the desired qualities before applying cement-based tiles adhesive.

AREA OF APPLICATION

DW PRIMER can be applied as a primer layer in various supports, such as: old tiles, smooth surfaces, natural stones, floor surfaces of cement, wood and metal.

INSTRUCTIONS FOR PREPARATION

Support: the surface where DW PRIMER will be applied must be free of moisture, dust and without parts painted with oil.

APPLICATION

DW PRIMER is ready for use, and is applied directly to the support by means of a roller or brush. Tile adhesive can be applied after an hour, as long as DW PRIMER is sticky.

SHELF-LIFE STORAGE

The lifespan of product is 18 months after manufacture date, if stored in its original packaging and protected by frost and direct exposure to sun.

NOTE

Environment temperature during application should be between +5°C and 35°C. The maximal allowed time after application is 12 hours. If this time passes, then a new layer is necessary before the application of tile adhesive. DW PRIMER is indispensable when adhering tile to tile.

