

PAVING & STONE

BLACK STONE COLOUR RESTORER ECO/12



SEAL & PROTECT

Water-based black impregnating sealer.

For restoring the appearance of all types of faded dark natural and artificial stone including limestone, marble, slate, and concrete pavers.

DIRECTIONS FOR USE

Preparation: Ensure surface to be treated is completely clean, dry, and free from dirt, grime, cement, and grout. If necessary, first wash surfaces with a dilute solution of ECOPROTEC Intensive Cleaner 1:5 and scrub with a white nylon pad. Rinse well to remove residues and leave to dry.

Application: Wear gloves and ensure that any surfaces not to be treated are covered and protected.

IMPORTANT: This product is a permanent staining solution that will darken the surface of the stone and the grout joints making it very difficult to remove once applied. It is an impregnating sealer that needs to fully absorb into the stone. It is not film forming, so any excess left on the surface should be removed. Always test on a small area before general application to help establish best method and optimum number of coats required. Do not walk on treated surfaces until the solution has completely dried.

Shake bottle well before use. Work in manageable areas at a time as far as you can reach without stepping into the solution. Apply a small amount to the surface and spread out evenly using a sealant applicator, foam roller or paint brush.

Allow to penetrate the stone. If a second coat is required apply immediately after the first has absorbed. Do not allow the first coat to fully dry before application.

Do not walk on the surface for at least 4 hours after the final application. Once dry and to help ensure an even application it may be necessary to work off any visible excess using a dry towel. Allow newly treated surfaces to cure for 24 hours. If necessary, wash surfaces with a 1 : 10 dilute solution of ECOPROTEC Intensive Cleaner. This will help to remove any excess that is difficult to rub off. Before allowing traffic gently rub the surface in a few areas with white cloth or paper towel to make sure that it is colourfast.

Do not use when surfaces are very cold or very hot. Ideally between 5 - 25°C.

COVERAGE

Up to 30 sq. M per litre per coat.

STORAGE INFORMATION

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 2 years for un-opened containers.

HEALTH, SAFETY & ENVIRONMENTAL

Contains: 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5).

Keep out of reach of children. May produce an allergic reaction.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.