

## **mira safe coat**

Artificial fibre strip / mat used as a carrying layer for the product **mira 4400 multicoat**

### **Characteristics**

- flexible, tension - resistant
- open fibre structure allows absorption of **mira 4400 multicoat**

### **Use**

10 cm wide strip is applied as a carrying layer for **mira 4400 multicoat** in wall corners, connections of floor and wall, joints between panels or elements, pipe or balustrade junctions, bathroom outlets etc. 100 cm wide mat applied as a carrying layer on floors ensures proper and uniform membrane thickness and results in quick drying.

### **Technical conditions**

- a. Fitting:  
Cut with sharp knife or scissors.

### **Technical data**

Weight:	100 g/m <sup>2</sup>
Thickness:	0,6 mm
Tension force (strip-test EN/ISO 10319):	
- Longitudinal and transverse direction:	3 kN/m.
Break extension:	35/45 %

### **Packing:**

Rolls dimension:  
strip: - 10 cm x 25 m.  
          10 cm x 100 m.  
mat: - 100 cm x 10 m.  
       100 cm x 50 m.

### **Storage and transportation:**

Protect from sunrays.

### **Industrial safety:**

Strip / mat contains no harmful substances, thus no special safety means shall be used.

### **Certificates:**

**PL:** Hygiene Evaluation PZH No. HK/B/1885/04/98